

## § 960.5-2

(2) *Environment, socioeconomics, and transportation.* During repository siting, construction, operation, closure, and decommissioning the public and the environment shall be adequately protected from the hazards posed by the disposal of radioactive waste.

(3) *Ease and cost of siting, construction, operation, and closure.* Repository siting, construction, operation, and closure shall be demonstrated to be technically feasible on the basis of reasonably available technology, and the associated costs shall be demonstrated to be reasonable relative to other available and comparable siting options.

### § 960.5-2 Technical guidelines.

The technical guidelines in this subpart set forth qualifying, favorable, potentially adverse, and, in seven guidelines, disqualifying conditions for the characteristics, processes, and events that influence the suitability of a site relative to the preclosure system guidelines. These conditions are separated into three main groups: Preclosure radiological safety; environment, socioeconomics, and transportation; and ease and cost of siting, construction, operation, and closure. The first group includes conditions on population density and distribution, site ownership and control, meteorology, and offsite installations and operations. The second group includes conditions related to environmental quality and socioeconomic impacts in areas potentially affected by a repository and to the transportation of waste to a repository site. The third group includes conditions on the surface characteristics of the site, the characteristics of the host rock and surrounding strata, hydrology, and tectonics. The individual technical guidelines within each group, as well as the favorable conditions and the potentially adverse conditions under each guideline, are not listed in any assumed order of importance. The technical guidelines that follow establish conditions that shall be considered in determining compliance with the qualifying conditions of the preclosure system guidelines. For each technical guideline, an evaluation of qualification or disqualification

shall be made in accordance with the requirements specified in subpart B.

### PRECLOSURE RADIOLOGICAL SAFETY

#### § 960.5-2-1 Population density and distribution.

(a) *Qualifying condition.* The site shall be located such that, during repository operation and closure, (1) the expected average radiation dose to members of the public within any highly populated area will not be likely to exceed a small fraction of the limits allowable under the requirements specified in § 960.5-1(a)(1), and (2) the expected radiation dose to any member of the public in an unrestricted area will not be likely to exceed the limit allowable under the requirements specified in § 960.5-1(a)(1).

(b) *Favorable conditions.* (1) A low population density in the general region of the site.

(2) Remoteness of site from highly populated areas.

(c) *Potentially adverse conditions.* (1) High residential, seasonal, or daytime population density within the projected site boundaries.

(2) Proximity of the site to highly populated areas, or to areas having at least 1,000 individuals in an area 1 mile by 1 mile as defined by the most recent decennial count of the U.S. census.

(d) *Disqualifying conditions.* A site shall be *disqualified* if—

(1) Any surface facility of a repository would be located in a highly populated area; or

(2) Any surface facility of a repository would be located adjacent to an area 1 mile by 1 mile having a population of not less than 1,000 individuals as enumerated by the most recent U.S. census; or

(3) The DOE could not develop an emergency preparedness program which meets the requirements specified in DOE Order 5500.3 (Reactor and Non-Reactor Facility Emergency Planning, Preparedness, and Response Program for Department of Energy Operations) and related guides or, when issued by the NRC, in 10 CFR part 60, subpart I, "Emergency Planning Criteria."